



SuperFlex[™] Housings



Facet SuperFlex housings are small, economical, carbon steel housings that may be used as filters, filter separators or air/gas separators depending on the cartridges used. Stainless steel construction is available. Contact your Facet Representative for details.

Liquid Filtration

MS Series SuperFlex Filters remove solids from liquids, compressed air or natural gas. Facet's M Series (high efficiency, screen wrapped or multipleated) cartridges, stacked 1, 2 or 3 high, are used.

Liquid-Liquid Separation

VCS Series SuperFlex Filter Separators remove water and solids from gasoline, diesel fuel, fuel oil, insulating oil, kerosene, lube oils, solvents and many other petroleum based products where water content is a problem. This housing requires Facet Model CC-23-7 or CC-23C coalescer cartridges and Model CS-94 or CS-94C pleated paper separator cartridges, stacked 1, 2 or 3 high.

Air/Gas Separation

AGS Series SuperFlex Air/Gas Separators remove oil, water, mist and solids from compressed air or natural gas. This housing requires Facet Model CC-23-7 coalescer cartridge and Model CS- 98-2 pleated paper separator cartridge.

Standard Housing Design Features

- Welded carbon steel construction
- ASME Code, Section VIII, Div. 1, stamped and certified
- Designed for 250 psi @ 250 °F (17.23 bar @ 121 °C)
- Main closure: Blind flange
- Head gasket: Buna-N o-ring —other materials available on request
- Vent connections: 3/4" NPT
- Drain connections: 3/4" 3000# NPT
- Inlet and outlet connections: 2" 3000# NPT
- Interior: Epoxy coatedExterior: Shop primer

Options

- 304 stainless steel construction
- Air eliminator
- Drain valve
- Pressure gauge assembly
- Pressure relief valve
- · Adjustable support stand


www.facetfiltration.com Industrial Applications

SuperFlex[™] Housings

DATA

HOUSING MODEL	HOUSING ONLY	ADAPTOR KIT	ADAPTOR KIT	HOUSING WEIGHT		HOUSING LIQUID VOLUME				
NUMBER	PART NUMBER	MODEL NUMBER	PART NUMBER	lbs	kg	gal	Itr			
LIQUID FILTRATION										
MS-1C-A	910000-1	MS-1CK	690542	120	54	7	26.5			
MS-2C-A	910000-2	MS-2CK	686497	140	63	10.5	39.7			
MS-3C-A	910000-3	MS-3CK	681021	160	72	14	53			
LIQUID-LIQUID SEPARATION										
VCS-1C-A	910000-1	VCS-1CK	676347	120	54	7	26.5			
VCS-2C-A	910000-2	VCS-2CK	676348	140	63	10.5	39.7			
VCS-3C-A	910000-3	VCS-3CK	676349	160	72	14	53			
AIR/GAS SEPARATION										
AGS-1C-A	910000-1	AGS-1CK	676347	120	54	7	26.5			
AGS-2C-A	910000-2	AGS-2CK	676348	140	63	10.5	39.7			
AGS-3C-A	910000-3	AGS-3CK	676349	160	72	14	53			

Weights and volumes are aproximate.



DIMENSIONS

HOUSING	A		В		С		D		E	
	in	mm	in	mm	in	mm	in	mm	in	mm
1 High	8 5/8	219	11 %	295	35 ¾	898	36 1/8	917	7 1/8	181
2 High	8 5/8	219	11 %	295	49 %	1267	50 %	1286	7 1/8	181
3 High	8 5/8	219	11 %	295	63 1/8	1622	64 %	1641	7 1/8	181

All dimensions are for estimating purposes only.

Industrial Applications www.facetfiltration.com